



NOTE:
ALL REINFORCEMENT SHOWN IS INDICATIVE ONLY. ADDITIONAL REINFORCEMENT MAY BE NEEDED TO MEET SPECIFIC REQUIREMENTS (E.G. STRENGTH, STABILITY, DURABILITY, APPEARANCE, ETC.) RELEVANT TO THE ELEMENT BEING DESIGNED, AND TO ENSURE THAT THE DESIGN IS FIT FOR PURPOSE. FINAL DESIGN TO BE OVERSEEN BY AN APPROPRIATELY QUALIFIED STRUCTURAL ENGINEER.

50mm EPS VH GRADE INFORMATION.
COMPRESSIVE STRENGTH 165 KPA AT 10% DEFORMATION (MIN). 2%
DEFORMATION GIVES 100 KPA COMPRESSIVE STRENGTH.
THIS VALUE WILL ONLY EXPERIENCE 1-2mm OVERALL DEFLECTION R-VALUE 1.43.

MEGAFOUND 280 SERIES FOUNDATION AT 800 HIGH INCORPORATING 430 SERIES RAFT

MEGAFORM NZ LTD ©
WWW.MEGAFOUND.CO.NZ
INFO@MEGAFOUND.CO.NZ
VERSION 10 FEB 2023